



Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Product name : Form Oil

1.2. Recommended use and restrictions on use

Recommended use : Lubricant

1.3. Supplier

Supplier

Irving Blending & Packaging
555 Courtenay Bay Causeway
Saint John, NB, E2L 4E6
CA
T 1.800.574.5823

Distributor

Irving Oil Terminals Inc.
190 Commerce Way
Portsmouth, NH
USA, 03801-3281

1.4. Emergency telephone number

Emergency number : 1.800.424.9300 (CHEMTREC)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA/US)

Flammable liquids Category 4
Skin sensitization, Category 1
Specific target organ toxicity (repeated exposure) Category 1

Aspiration hazard Category 1

Combustible liquid
May cause an allergic skin reaction
Causes damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation)
May be fatal if swallowed and enters airways

2.2. GHS Label elements, including precautionary statements

GHS CA/US labeling

Hazard pictograms (GHS CA/US)



Signal word (GHS CA/US)

: Danger

Hazard statements (GHS CA/US)

: Combustible liquid
May be fatal if swallowed and enters airways
May cause an allergic skin reaction
Causes damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation)

Precautionary statements (GHS CA/US)

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not breathe vapors, mist.
Wash hands, forearms and face thoroughly after handling.
Do not eat, drink or smoke when using this product.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves, protective clothing, eye protection, face protection.
In case of fire: Use media other than water to extinguish.
IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Do NOT induce vomiting.

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

IF ON SKIN: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice or attention.
Specific treatment (see supplemental first aid instruction on this label).
Get medical advice or attention if you feel unwell.
Store in a well-ventilated place.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA/US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Common Name (Synonyms)	Product identifier	%
Distillates, petroleum, hydrotreated heavy paraffinic	Petroleum distillates, hydrotreated heavy paraffinic / Distillates (petroleum), hydrotreated heavy paraffinic / Paraffin oil / Distillates, petroleum, hydrotreated heavy paraffinic (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20-50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.) / Heavy paraffinic hydrotreated distillate / HYDROGENATED MINERAL OIL / Hydrogenated mineral oil	CAS-No.: 64742-54-7	10 - 30
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy		CAS-No.: 64742-70-7	10 - 30

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Name	Common Name (Synonyms)	Product identifier	%
Stoddard solvent	White spirit / Mineral turpentine / Mineral spirits / White spirits / Turpentine, mineral / Turpentine (mineral) / Stoddard solvent (A colorless, refined petroleum distillate that is free from rancid or objectionable odors and that boils in the range of approximately 149-204.5°C.) / Naphtha, Stoddard solvent / White spirit type 1 / Stoddard solvent; Low boiling point naphtha -; unspecified [A colourless, refined petroleum distillate that is free from rancid or objectionable odours and that boils in a range of approximately 148.8°C to 204.4°C (300°F to 400°F).] / white spirit type 1	CAS-No.: 8052-41-3	10 - 30
Petroleum distillates, hydrotreated light	Hydrotreated light distillate / Kerosene, hydrotreated / Petroleum distillates, hydrotreated light (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9-16 and boiling in the range of approximately 150-290°C.) / Odorless light petroleum hydrocarbons / Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, / Kerosene / c13-14 isoparaffin / Destillate (Erdöl), mit Wasserstoff behandelt leichte (C9-14 Aliphaten) / Light Aliphatic Hydrocarbon / Odourless light petroleum hydrocarbons / Distillates (petroleum), hydro-treated light; Kerosine - unspecified [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (302°F to 554°F).] / Distillates, petroleum, hydrotreated light / Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	3 - 13
Nonane	NONANE / n-Nonane	CAS-No.: 111-84-2	0.5 - 1.5

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Name	Common Name (Synonyms)	Product identifier	%
Benzene, 1,2,4-trimethyl-	Trimethylbenzene, 1,2,4- / Trimethylbenzene / 1,2,4- Trimethylbenzene / Pseudocumene	CAS-No.: 95-63-6	0.5 - 1.5
Rosin	Gum rosin / Colophony / Colophonium / Rosin, gum / COLOPHONIUM / Rosin (pinus species) and rosin derivatives / ROSIN / Gum resin / Resin acids / Rosin (Pinus species)	CAS-No.: 8050-09-7	< 1
Naphthalene	Naphthalene, molten / Naphthalene, crude / Naphthalenes / Moth balls	CAS-No.: 91-20-3	< 0.5
Ethylbenzene	Benzene, ethyl- / Phenylethane / ETHYLBENZENE	CAS-No.: 100-41-4	< 0.2

Comments : All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.
CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical help.

First-aid measures after eye contact : Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation persists.

First-aid measures after ingestion : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. If vomiting occurs have person lean forward. Never give anything by mouth to an unconscious person.

First-aid measures general : Call a physician immediately. If you feel unwell, seek medical advice (show the label where possible). Medical personnel should be made aware of substance(s) involved and take measures for self protection. Show this safety data sheet to the doctor in attendance. Avoid contact with skin and eyes. Keep out of the reach of children.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Prolonged inhalation may be harmful.

Symptoms/effects after skin contact : Prolonged or repeated contact may dry skin and cause irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Direct contact with eyes may cause temporary irritation.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May cause stomach distress, nausea or vomiting.

Chronic symptoms : Causes damage to organs through prolonged or repeated exposure.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Symptoms may be delayed. Treat symptomatically.

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Treat for surrounding material.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Combustible liquid. During fire, gases hazardous to health may be formed. In case of fire or explosion do not breathe fumes.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : May include and are not limited to: oxides of carbon.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Keep unnecessary personnel away. For personal protection, see section 8 of the SDS. In the event of a significant spillage : Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leaks if it can be done without personal risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean contaminated surfaces with an excess of water. Notify authorities if product enters sewers or public waters.
Other information : This material and its container must be disposed of in a safe way, and as per local legislation.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes. Do not taste or swallow. Ensure good ventilation of the work station. Wear personal protective equipment. Handle and open container with care.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Keep out of reach of children. Store tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Nonane (111-84-2)	
Canada (Alberta) - Occupational Exposure Limits	
OEL TWA	1050 mg/m ³
	200 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
VEMP (OEL TWAEV)	1050 mg/m ³
	200 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
OEL TWA	200 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
OEL TWA	200 ppm
Notations and remarks	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2024
Canada (New Brunswick) - Occupational Exposure Limits	
OEL TWA	200 ppm
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
OEL TWA	200 ppm
Notations and remarks	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
OEL TWA	200 ppm
Notations and remarks	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
OEL TWA	200 ppm (Nonane, all isomers)
OEL STEL	250 ppm (Nonane, all isomers)
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
OEL TWA	200 ppm (Nonane, all isomers)
OEL STEL	250 ppm (Nonane, all isomers)
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Nonane (111-84-2)	
Canada (Ontario) - Occupational Exposure Limits	
OEL TWAEV	200 ppm
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
OEL TWA	200 ppm
Notations and remarks	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
OEL TWA	200 ppm
OEL STEL	250 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Canada (Yukon) - Occupational Exposure Limits	
OEL TWA	1050 mg/m³
	200 ppm
OEL STEL	1300 mg/m³
	250 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	200 ppm
Remark (ACGIH)	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2024
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	1050 mg/m³
	200 ppm
US-NIOSH chemical category	SK: DIR(IRR) Apr 2011
Benzene, 1,2,4-trimethyl- (95-63-6)	
Canada (Manitoba) - Occupational Exposure Limits	
OEL TWA	10 ppm (Trimethylbenzene, isomers)
Notations and remarks	TLV® Basis: CNS impair; hematologic eff. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
OEL TWA	10 ppm (Trimethylbenzene, isomers)
Notations and remarks	TLV® Basis: CNS impair; hematologic eff. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
OEL TWA	10 ppm (Trimethylbenzene, isomers)

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Benzene, 1,2,4-trimethyl- (95-63-6)	
Notations and remarks	TLV® Basis: CNS impair; hematologic eff. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Prince Edward Island) - Occupational Exposure Limits	
OEL TWA	10 ppm (Trimethylbenzene, isomers)
Notations and remarks	TLV® Basis: CNS impair; hematologic eff. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 ppm (Trimethylbenzene, isomers)
Remark (ACGIH)	TLV® Basis: CNS impair; hematologic eff. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2024
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	125 mg/m³
	25 ppm
Naphthalene (91-20-3)	
Canada (Alberta) - Occupational Exposure Limits	
OEL TWA	52 mg/m³
	10 ppm
OEL STEL	79 mg/m³
	15 ppm
Notations and remarks	Substance may be readily absorbed through intact skin.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
VEMP (OEL TWA EV)	10 ppm
Notations and remarks	C3, Pc
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
OEL TWA	10 ppm
Notations and remarks	Skin; IARC group 2B carcinogen
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
OEL TWA	10 ppm
Notations and remarks	TLV® Basis: URT irr; cararacts; hemolytic anemia. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Naphthalene (91-20-3)	
Canada (New Brunswick) - Occupational Exposure Limits	
OEL TWA	10 ppm
Notations and remarks	Hematologic eff; URT & eye irr; Skin; A3
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
OEL TWA	10 ppm
Notations and remarks	TLV® Basis: URT irr; cararacts; hemolytic anemia. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
OEL TWA	10 ppm
Notations and remarks	TLV® Basis: URT irr; cararacts; hemolytic anemia. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
OEL TWA	10 ppm
OEL STEL	15 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
OEL TWA	10 ppm
OEL STEL	15 ppm
Notations and remarks	Skin
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Canada (Ontario) - Occupational Exposure Limits	
OEL TWAEV	10 ppm
Notations and remarks	Skin
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
OEL TWA	10 ppm
Notations and remarks	TLV® Basis: URT irr; cararacts; hemolytic anemia. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
OEL TWA	10 ppm
OEL STEL	15 ppm
Notations and remarks	Skin

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Naphthalene (91-20-3)	
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Canada (Yukon) - Occupational Exposure Limits	
OEL TWA	50 mg/m ³
	10 ppm
OEL STEL	75 mg/m ³
	15 ppm
Regulatory reference	Occupational Health Regulations, YOIC 1986D/164
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 ppm
Remark (ACGIH)	TLV® Basis: URT irr; cararacts; hemolytic anemia. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans, Skin - potential significant contribution to overall exposure by the cutaneous route
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	Naphthalene
BEI	Parameter: 1-Naphthol + 2-Naphthol (with hydrolysis) - Sampling time: End of shift - Notations: Nq, Ns
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	50 mg/m ³
	10 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	250 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	50 mg/m ³
	10 ppm
NIOSH REL STEL	75 mg/m ³
	15 ppm
Stoddard solvent (8052-41-3)	
Canada (Alberta) - Occupational Exposure Limits	
OEL TWA	572 mg/m ³
	100 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
VEMP (OEL TWA EV)	525 mg/m ³

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Stoddard solvent (8052-41-3)	
	100 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
OEL TWA	290 mg/m ³
OEL STEL	580 mg/m ³
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Eye, skin, & kidney dam; nausea; CNS impair
Regulatory reference	ACGIH 2024
Canada (New Brunswick) - Occupational Exposure Limits	
OEL TWA	100 ppm
Notations and remarks	Eye, skin, & kidney dam;
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Eye, skin, & kidney dam; nausea; CNS impair
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Eye, skin, & kidney dam; nausea; CNS impair
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
OEL TWA	100 ppm
OEL STEL	125 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
OEL TWA	100 ppm
OEL STEL	125 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Canada (Ontario) - Occupational Exposure Limits	
OEL TWAEV	525 mg/m ³ (140°F Flash aliphatic solvent)
	100 ppm
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Eye, skin, & kidney dam; nausea; CNS impair
Regulatory reference	ACGIH 2024

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Stoddard solvent (8052-41-3)	
Canada (Saskatchewan) - Occupational Exposure Limits	
OEL TWA	100 ppm
OEL STEL	125 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Canada (Yukon) - Occupational Exposure Limits	
OEL TWA	575 mg/m³
	100 ppm
OEL STEL	720 mg/m³
	150 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	100 ppm
Remark (ACGIH)	TLV® Basis: Eye, skin, & kidney dam; nausea; CNS impair
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	2900 mg/m³
	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	20000 mg/m³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	350 mg/m³
NIOSH REL C	1800 mg/m³
Ethylbenzene (100-41-4)	
Canada (Alberta) - Occupational Exposure Limits	
OEL TWA	434 mg/m³
	100 ppm
OEL STEL	543 mg/m³
	125 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
VEMP (OEL TWAEV)	20 ppm
Notations and remarks	C3
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
OEL TWA	20 ppm
Notations and remarks	IARC group 2B carcinogen

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Ethylbenzene (100-41-4)	
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: URT & eye irr; ototoxicity; kidney eff; CNS impair. Notations: OTO (Ototoxicant); A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024
Canada (New Brunswick) - Occupational Exposure Limits	
OEL TWA	20 ppm
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: URT & eye irr; ototoxicity; kidney eff; CNS impair. Notations: OTO (Ototoxicant); A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: URT & eye irr; ototoxicity; kidney eff; CNS impair. Notations: OTO (Ototoxicant); A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
OEL TWA	100 ppm
OEL STEL	125 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
OEL TWA	100 ppm
OEL STEL	125 ppm
Notations and remarks	Designated substance
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Canada (Ontario) - Occupational Exposure Limits	
OEL TWAEV	20 ppm
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: URT & eye irr; ototoxicity; kidney eff; CNS impair. Notations: OTO (Ototoxicant); A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
OEL TWA	100 ppm
OEL STEL	125 ppm

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Ethylbenzene (100-41-4)	
Notations and remarks	Designated Chemical Substance
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Canada (Yukon) - Occupational Exposure Limits	
OEL TWA	435 mg/m³
	100 ppm
OEL STEL	545 mg/m³
	125 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	20 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; ototoxicity; kidney eff; CNS impair. Notations: OTO (Ototoxicant); A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	Ethyl benzene
BEI	0.15 g/g Kreatinin Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: end of shift (nonspecific)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	435 mg/m³
	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	800 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	435 mg/m³
	100 ppm
NIOSH REL STEL	545 mg/m³
	125 ppm
Rosin (8050-09-7)	
Canada (Quebec) - Occupational Exposure Limits	
Notations and remarks	Without applicable permissible exposure value; S(D), S(R)
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Notations and remarks	No exposure limit. Exposure by all routes should be carefully controlled to levels as low as possible. S(D) (dermal sensitization); S(R) (respiratory sensitization)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Rosin (8050-09-7)	
Canada (Manitoba) - Occupational Exposure Limits	
OEL TWA	0.001 mg/m³ (I - Inhalable particulate matter)
Notations and remarks	TLV® Basis: Asthma; resp & eye irr; dermal & resp sens. Notations: DSEN; RSEN
Regulatory reference	ACGIH 2024
Canada (New Brunswick) - Occupational Exposure Limits	
Notations and remarks	DSEN; RSEN
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
OEL TWA	0.001 mg/m³ (I - Inhalable particulate matter)
Notations and remarks	TLV® Basis: Asthma; resp & eye irr; dermal & resp sens. Notations: DSEN; RSEN
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
OEL TWA	0.001 mg/m³ (I - Inhalable particulate matter)
Notations and remarks	TLV® Basis: Asthma; resp & eye irr; dermal & resp sens. Notations: DSEN; RSEN
Regulatory reference	ACGIH 2024
Canada (Ontario) - Occupational Exposure Limits	
Notations and remarks	(L) Exposure by all routes should be carefully controlled to levels as low as possible.
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
OEL TWA	0.001 mg/m³ (I - Inhalable particulate matter)
Notations and remarks	TLV® Basis: Asthma; resp & eye irr; dermal & resp sens. Notations: DSEN; RSEN
Regulatory reference	ACGIH 2024
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.001 mg/m³ (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: Asthma; resp & eye irr; dermal & resp sens. Notations: DSEN; RSEN
ACGIH chemical category	dermal sensitizer
Regulatory reference	ACGIH 2024

8.2. Appropriate engineering controls

Appropriate engineering controls	: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Wear suitable gloves resistant to chemical penetration

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Eye protection:

Wear eye protection

Skin and body protection:

Wear suitable protective clothing. As required by employer code.

Respiratory protection:

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 65 °C PMCC (ASTM D93a)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Combustible liquid
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 0.8461 kg/l @ 15°C (ASTM 4052)
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 6.17 mm²/s @ 40°C (ASTM D445)
Explosive properties	: Not explosive.
Oxidizing properties	: Not oxidising.
Explosion limits	: No data available

9.2. Other information

Pour point	: -33 °C ASTM D97
------------	-------------------

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Keep away from heat and direct sunlight. Do not mix with other chemicals. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Strong oxidizing agents.

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Hazardous decomposition products : May include and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Unknown acute toxicity (GHS CA/US)	Not applicable
------------------------------------	----------------

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 15 g/kg (Source: EPA_HPVS)
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HPVS)
LC50 Inhalation - Rat	2.18 mg/l
LC50 Inhalation - Rat (Vapours)	2.18 mg/l/4h

Nonane (111-84-2)	
LC50 Inhalation - Rat [ppm]	3200 ppm/4h

Benzene, 1,2,4-trimethyl- (95-63-6)	
LD50 oral rat	3280 mg/kg (Source: NZ_CCID)
LD50 dermal rat	3440 mg/kg (24 h, Rat, Male / female, Read-across, Dermal)
LD50 dermal rabbit	> 3160 mg/kg (Source: IUCLID)
LC50 Inhalation - Rat	18 g/m³ (Exposure time: 4 h Source: NLM_CIP)

Naphthalene (91-20-3)	
LD50 oral rat	1110 mg/kg (Source: JAPAN_GHS)
LD50 oral	533 mg/kg body weight (Equivalent or similar to OECD 401, Mouse, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 16000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LD50 dermal rabbit	2500 mg/kg Source: ChemIDplus
LC50 Inhalation - Rat	> 0.4 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, (maximum achievable concentration), Inhalation (vapours), 14 day(s))
LC50 Inhalation - Rat (Vapours)	> 0.4 mg/l Source: ECHA
ATE CA (oral)	533 mg/kg body weight
ATE CA (Dermal)	2500 mg/kg body weight
ATE CA (dust,mist)	0.05 mg/l/4h

Stoddard solvent (8052-41-3)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 3000 mg/kg (Source: ECHA_API)

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Stoddard solvent (8052-41-3)	
LC50 Inhalation - Rat	> 5.5 mg/l/4h

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg (Source: IUCLID)
LD50 dermal rabbit	> 2000 mg/kg (Source: NLM_CIP)
LC50 Inhalation - Rat	> 5.2 mg/l/4h

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	15400 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat	17.4 mg/l/4h
ATE CA (oral)	3500 mg/kg body weight
ATE CA (Dermal)	15400 mg/kg body weight
ATE CA (Gases)	4500 ppmV/4h
ATE CA (vapors)	17.4 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h

Rosin (8050-09-7)	
LD50 oral rat	7600 mg/kg (Source: CHEMVIEW)
LD50 dermal rabbit	> 2500 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat	1.5 mg/l/4h
ATE CA (oral)	7600 mg/kg body weight
ATE CA (vapors)	1.5 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Respiratory sensitization: Not classified. May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified.

Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	Reasonably anticipated to be Human Carcinogen, Evidence of Carcinogenicity

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Benzene, 1,2,4-trimethyl- (95-63-6)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Causes damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).

Benzene, 1,2,4-trimethyl- (95-63-6)	
NOAEL (oral,rat,90 days)	600 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,vapor,90 days)	1.8 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)

Naphthalene (91-20-3)	
LOAEL (oral,rat,90 days)	400 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
LOAEC (inhalation,rat,vapor,90 days)	0.011 mg/l air Animal: rat, Guideline: EPA OPP 82-4 (90-Day Inhalation Toxicity), Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral,rat,90 days)	200 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Stoddard solvent (8052-41-3)	
NOAEL (oral,rat,90 days)	1056 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Ethylbenzene (100-41-4)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.
Likely routes of exposure : Skin and eye contact. Ingestion. Inhalation.
Symptoms/effects after inhalation : Prolonged inhalation may be harmful.
Symptoms/effects after skin contact : Prolonged or repeated contact may dry skin and cause irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Direct contact with eyes may cause temporary irritation.
Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May cause stomach distress, nausea or vomiting.
Chronic symptoms : Causes damage to organs through prolonged or repeated exposure.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : See below for route-specific details.
Hazardous to the aquatic environment, short-term (acute) : Not classified.

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Hazardous to the aquatic environment, long-term : Not classified.
(chronic)

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: IUCLID)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Benzene, 1,2,4-trimethyl- (95-63-6)	
LC50 - Fish [1]	7.19 – 8.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 96h - Algae [1]	2.356 mg/l (ECOSAR, Algae, Fresh water, QSAR)

Naphthalene (91-20-3)	
LC50 - Fish [1]	0.96 ppm (Oncorhynchus gorbuscha, Flow-through system, Salt water, Experimental value, Lethal)
LC50 - Fish [2]	1.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: EPA)
EC50 - Crustacea [1]	2.16 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 - Crustacea [2]	1.96 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])
EC50 72h - Algae [1]	0.4 mg/l (Skeletonema costatum, Literature study, Growth rate)
NOEC (chronic)	0.59 mg/l Test organisms (species): Daphnia pulex Duration: '125 d'

Stoddard solvent (8052-41-3)	
LC50 - Fish [1]	2.5 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 96h - Algae [1]	0.58 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	0.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 - Fish [1]	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: IUCLID)
LC50 - Fish [2]	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)

Ethylbenzene (100-41-4)	
LC50 - Fish [1]	11 – 18 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
LC50 - Fish [2]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static] Source: EPA)
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	4.6 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 72h - Algae [2]	2.6 – 11.3 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h - Algae [1]	> 438 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h - Algae [2]	1.7 – 7.6 mg/l (Species: Pseudokirchneriella subcapitata [static])

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

Rosin (8050-09-7)

EC50 - Crustacea [1]	3.8 – 5.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	400 mg/l (Species: Desmodesmus subspicatus)

12.2. Persistence and degradability

Benzene, 1,2,4-trimethyl- (95-63-6)

Persistence and degradability	Not readily biodegradable in water.
Chemical oxygen demand (COD)	0.44 g O ₂ /g substance

Naphthalene (91-20-3)

Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0 g O ₂ /g substance
Chemical oxygen demand (COD)	0.22 g O ₂ /g substance
ThOD	2.99 g O ₂ /g substance

12.3. Bioaccumulative potential

Benzene, 1,2,4-trimethyl- (95-63-6)

Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
BCF - Fish [1]	243 (Pimephales promelas, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3.63

Naphthalene (91-20-3)

Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	23 – 168 (OECD 305: Bioconcentration: Flow-Through Fish Test, 8 week(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.4 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)

Stoddard solvent (8052-41-3)

Partition coefficient n-octanol/water (Log Pow)	6.4 (at 20 °C)
---	----------------

Petroleum distillates, hydrotreated light (64742-47-8)

BCF - Fish [1]	61 – 159
----------------	----------

Ethylbenzene (100-41-4)

BCF - Fish [1]	(15 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	3.6 (at 20 °C (at pH 7.84)

Rosin (8050-09-7)

Partition coefficient n-octanol/water (Log Pow)	(>1.9 - <=7.7 (at pH 2)
---	-------------------------

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

12.4. Mobility in soil

Benzene, 1,2,4-trimethyl- (95-63-6)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil. May be harmful to plant growth, blooming and fruit formation.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.04 (log Koc, Calculated value)

Naphthalene (91-20-3)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for adsorption in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.864 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of the material collected according to regulations.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling, disposal or collection. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14: Transport information

TDG	DOT	IMDG	IATA
14.1. UN number			
Not regulated	Not applicable	Not regulated	Not regulated
14.2. Proper Shipping Name			
Not regulated	Not applicable	Not regulated	Not regulated
Transport document description			
Not regulated	1993, 3, I	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	3	Not regulated	Not regulated
14.4. Packing group			
Not regulated	I	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Dangerous for the environment: No	Not regulated	Not regulated
No supplementary information available			

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

14.6. Special precautions for user

TDG
Not regulated

DOT
UN-No.(DOT) : 1993

IMDG
Not regulated

IATA
Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

All components of this product are present on DSL

Naphthalene (91-20-3)	
Toxic Substance (CEPA – Schedule I)	Yes

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
Benzene, 1,2,4-trimethyl-	CAS-No. 95-63-6	0.5 - 1.5%
Naphthalene	CAS-No. 91-20-3	< 0.5%
Ethylbenzene	CAS-No. 100-41-4	< 0.2%

**WARNING:**

This product can expose you to Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Issue date : 07/29/2024
Revision date : 07/29/2024

Other information : For an updated SDS, please contact the supplier or manufacturer listed on the first page of the document.

Form Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)
Issue date: 7/29/2024 Revision date: 7/29/2024 Version: 1.0

The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.